

Screen Degreaser Conc. No. 33

Cleaning and degreasing concentrate (1:10) for screen-printing mesh; native raw materials

Screen Degreaser Conc. No. 33 is a highly efficient cleaning and degreasing concentrate for screen meshes. It is used in a dilution of 1:10 with water. **Screen Degreaser Conc. No. 33** solutions emulsify contamination and fats and thus make them water soluble. Its formulation has especially been adapted to meet with the requirements of screen printing. Screen Degreaser Conc. No. 33 is therefore better than all conventional detergents. It is suitable for all mesh types and prevents the appearance of pinholes and surface deterioration when coating with direct photoemulsions. In its formulation, mainly components, which are either made of renewable raw materials or produced with biotechnology were used. **Screen Degreaser Conc. No. 33** is pH-neutral, free from phosphates and chlorides and is easily biodegradable.

APPLICATION

Before use, dissolve **Screen Degreaser Conc. No. 33** in water in a ratio of 1:10. To avoid strong foaming, pour the concentrate into water and not vice versa.

Apply a few squirts of the reduced solution onto the screen and brush well onto both sides until the resulting foam has been evenly distributed. Rinse with water until it runs off without foam. After drying, the screen can be coated. The foam very quickly disappears in the waste water.

It is recommended to clean/degrease the mesh just prior to coating to prevent fresh contamination of the mesh.

COLOUR	Yellowish
CONSISTENCY	Viscous liquid
HEALTH HAZARDS/ ENVIRONMENTAL PROTECTION	<p>When working with Screen Degreaser Conc. No. 33 it is recommended to wear safety goggles and gloves.</p> <p>Screen Degreaser Conc. No. 33 is biodegradable and can be emptied into drains in usual working dilution.</p> <p>Please follow further information given in the material safety data sheet.</p>
STORAGE	<p>2 years (at 20 - 25°C and tightly closed original container)</p> <p>Screen Degreaser Conc. No. 33 freezes at approx. 0°C. It can be applied again after thawing.</p>

This data sheet is for your information. A legally binding assurance of the product's suitability for a specific purpose cannot be derived from it and no liability can be assumed for any potential damages that may occur. Our products are subject to continuous production and quality control and leave our company in perfect condition.

This product is intended solely for industrial applications and not for use by the end consumer. We recommend to our customers to always test the product themselves since only in this way – also after production – can the freedom from certain substances and the suitability for a particular purpose be verified. The user has to test the product for suitability for the intended application. We reserve the right to modify product specifications. Tests that are not part of the specifications of the product mentioned above have not been carried out.

All information applies only to the above-mentioned product obtained from Kissel + Wolf GmbH. It corresponds to our current state of knowledge, but is not a confirmation of a particular application and is not automatically replenished. All information is valid for a maximum of 12 months (annexes may be provided with their own date) or until legal changes are made in this time period. The recipient of our product is solely responsible for observing any possible property rights as well as existing laws and regulations. Property rights of third parties must be observed. Our terms and conditions of sale and delivery shall apply.